

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) UK Patent Application (19) GB (11) 2 054 975 A

(21) Application No 7926320
(22) Date of filing 27 Jul 1979
(43) Application published
18 Feb 1981

(51) INT CL³
H02K 17/42

(52) Domestic classification
H2A ML
H2H AK

(56) Documents cited
GB 1538641
GB 932828
GB 873898

(58) Field of search
H2A
H2H

(71) Applicants
The English Electric
Company Limited, 1,
Stanhope Gate, London
W1A 1EH


(72) Inventor
James Joseph Raftery

(74) Agent
H. V. A. Kirby, Central
Patent Department, The
General Electric Co. Ltd.,
Hirst Research Centre,
Wembley, Middlesex,
HA9 7PP

(54) Alternating current generating
equipment

(57) An alternating current power
generating system incorporates a
generator (1) in the form of a dynamo-
electric machine having stator and
rotor windings wound as for a wound
rotor induction motor, and an exciter
(4) in the form of an induction motor
having its rotor coupled to that of the
generator with the rotor windings (3,
2) of both machines interconnected,
the stator winding of the generator
being connected to conductors (7) of a

three-phase supply of substantially
constant frequency, and the stator
winding of the exciter being
connected to control means (8) for
feeding the winding with alternating
current of controlled voltage and
frequency. By suitably controlling the
frequency supplied to the exciter the
output frequency from the generator
(1) can be maintained substantially
constant and equal to that of the
supply, provided the speed of the
generator rotor is above a certain
value. The system may be powered by
a turbine 6 driven by wind, wave or
tide power.




The drawing originally filed
was informal and the print here
reproduced is taken from a
later filed formal copy.

GB 2 054 975 A

///

2054975



SPECIFICATION

Power generating equipment

This invention relates to electrical power generating equipment.

- 5 On some types of power generating equipment the rotational speed of an alternating current generator may vary widely and in a random manner. Such applications include the harnessing of wave, wind and tidal power. In order to feed this power into the National Grid or to parallel a number of generators onto a common bus, the random frequency outputs from these generators must be converted into a common standard, that is 50 Hz in this country.

- 15 With present day technology the first approach would be to use a static method of conversion (rectifying and inverting) but this still has certain limitations regarding maximum available rating, cost reliability and control complexity.
- 20 According to the invention an alternating current electrical power generating system comprises a generator in the form of a dynamo-electric machine having stator and rotor windings wound as for a wound rotor induction motor, means for driving the rotor of the generator, an exciter in the form of an induction motor having its rotor rotatable with the generator rotor, for example by being mounted on the same shaft, with the rotor windings of the exciter and generator interconnected, the stator winding of the generator being connected to conductors of a three-phase supply of substantially constant frequency, and the stator winding of the exciter being connected to control means for feeding the winding with alternating current of controlled voltage and frequency.

- This arrangement can be regarded as consisting of an AC generator whose control field is also excited by AC in place of the more conventional DC, and by suitable control of the frequency supplied to the exciter the output frequency from the generator can be maintained substantially constant and equal to that of the supply, as long as the speed of rotation of the generator is above a certain value.

- Switching means can be provided for automatically cutting-off the generator from the constant frequency supply if its speed of rotation falls below said value in order to prevent power being taken from the supply in those circumstances.

- The invention will be further explained by describing by way of example, with reference to the accompanying schematic drawing, one form of alternating current generating arrangement in accordance with the invention.

- The arrangement comprises a main generator 1 in the form of a wound rotor induction motor having its rotor winding 2 connected to rotor winding 3 of an exciter 4 in the form of another

induction motor, the rotors of both machines being mounted on a common shaft 5. The rotor shaft is also coupled to driving means whose rotational speed may fluctuate in use.

- 65 The exciter 4 is fed from bus-bars 7 of a three phase constant frequency supply, and is phase and frequency controlled by a controller 8 to ensure a frequency of current in the rotor link of $F_s \pm NP$ where

- 70 F_s = frequency of the supply
N = speed of the generator and exciter rotors
P = number of poles of the generator and of the exciter.

- With such an arrangement, provided the speed of rotation of the generator is more than a predetermined value, power will be fed into the bus-bars 6 from the generator at the supply frequency, even though the generator speed varies.

- 80 Accordingly the invention is particularly suitable for use in systems where the means 6 for driving the generator operates at varying speeds, for example in the case of a turbine driven by wave, wind or tidal power. However the invention is also applicable to arrangements utilising other forms of drive means liable to speed fluctuations. It will be observed that since the rotor windings of the generator and exciter are interconnected the system avoids the use of slip rings.

90 CLAIMS

1. An alternating current power generating system comprising a generator in the form of a dynamo-electric machine having stator and rotor windings wound as for a wound rotor induction motor, means for driving the rotor of the generator, an exciter in the form of an induction motor having its rotor rotatable with the generator rotor, with the rotor windings of the exciter and generator interconnected, the stator winding of the generator being connected to conductors of a three-phase supply of substantially constant frequency, and the stator winding of the exciter being connected to control means for feeding the winding with alternating current of controlled voltage and frequency.

2. An alternating current power generating system according to Claim 1 including switching means for cutting off the generator from the constant frequency supply if its speed of rotation falls below a predetermined value.

3. An alternating current power generating system wherein the generator rotor is coupled to a turbine or other rotary device driven by wave, wind or tidal power.

4. An alternating current power generating system substantially as shown in and as hereinbefore described with reference to the accompanying drawing.